

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Crisine-Ultra

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Special purpose embalming chemical

Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

THE CHAMPION COMPANY
400 Harrison Street
Springfield, Ohio 45505Lucentt Limited
40 Ben Lomond Crescent
Auckland, New Zealand

Telephone No. (937) 324-5681

Phone: 09 273 8114

1.4. Emergency telephone number

INFOTRAC: 1-800-535-5053 DOMESTIC or 352-323-3500 INTERNATIONAL

National Poisons Centre 0800 764 766

Hazardous Substance Emergency 0800 CHEMCALL (0800 243 622)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3	H226
Acute Tox. 3 (Oral)	H301
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Corr. 1B	H314
Eye Dam. 1	H318
Muta. 2	H341
STOT SE 1	H370
STOT RE 2	H373

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS05

GHS06

GHS08

Signal word (GHS-US) :

: Danger

Hazard statements (GHS-US) :

: H226 - Flammable liquid and vapor
H301 - Toxic if swallowed
H312+H332 - Harmful in contact with skin or if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H341 - Suspected of causing genetic defects
H370 - Causes damage to organs (optic nerve, central nervous system)
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

: P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground container and receiving equipment
P241 - Use explosion-proof electrical, ventilating, lighting, and equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe dust, fume, mist, spray, vapors
P261 - Avoid breathing dust, fume, mist, spray, vapors

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only in a well-ventilated area
P280 - Wear protective clothing, protective gloves, eye protection, face protection.
P285 - In case of inadequate ventilation wear respiratory protection.
P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P307+P311 - If exposed: Call a doctor
P308+P313 - If exposed or concerned: Get medical attention
P310 - Immediately call a POISON CENTER
P312 - Call a POISON CENTER
P314 - Get medical attention if you feel unwell
P330 - Rinse mouth
P362 - Take off contaminated clothing and wash before reuse
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use alcohol resistant foam, dry powder, carbon dioxide (CO₂) powder to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methyl salicylate	(CAS No) 119-36-8	20 - 25	Acute Tox. 4 (Oral), H302
Phenol	(CAS No) 108-95-2	15 - 20	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Muta. 2, H341 STOT RE 2, H373
Ethylene glycol	(CAS No) 107-21-1	10 - 20	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Isopropyl alcohol	(CAS No) 67-63-0	5 - 9	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl alcohol	(CAS No) 67-56-1	5 - 9	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370
Cresol, all isomers	(CAS No) 1319-77-3	1 - 2	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a POISON CENTER.

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep victim warm and rested. Seek medical attention immediately. Immediately call a doctor. If breathing stops, give artificial respiration. Transfer to hospital rapidly.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash immediately with lots of water (15 minutes). Get medical attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Seek medical attention immediately. Transport to hospital.
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Immediately call a POISON CENTER. Take immediately victim to hospital. Seek medical advice (show the label where possible).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage. Suspected of causing genetic defects. Causes damage to organs.
Symptoms/injuries after inhalation	: Harmful if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. Excessive concentrations may cause nervous system depression, headache, and weakness leading to unconsciousness. Causes damage to liver through prolonged or repeated exposure if inhaled. Difficulty in breathing. Product contains phenol. Inhalation of phenol vapors can lead to damage of the bronchial system and pulmonary oedema. Systemic damage to kidneys, liver and heart as well as neuropsychiatric disturbances are produced.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Absorbed through the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Contains phenol. Strong skin absorption as main danger of phenol poisoning at the workplace with paralysis of the central nervous system (with lethal consequences in severe cases) as well as liver and kidney damage. Phenol destroys the nerve endings in the skin. Therefore absence of pain does not necessarily mean the skin has been properly decontaminated.
Symptoms/injuries after eye contact	: Redness and pain. Impaired vision, watering of eyes, defects in the cornea. Burning sensation. Inflammation. Can cause blindness. Causes serious eye damage.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death. Contains: Phenol and methanol. The swallowing of even a small amount of methanol can cause blindness or lead to death. The following may result in the case of a low dosage: nausea, headache, stomach-ache, vomiting and impaired vision (blurred vision, photophobia). There is furthermore risk of damage to liver, kidneys and heart. Effects may be delayed and manifest within 18 to 48 hours. Stinging sensation. Headache. Disorientation. Dizziness. Unconsciousness. Contains ethanol; constant ingestion of ethanol can lead to cirrhosis of the liver.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Thermal decomposition generates : Corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions	: Prevent runoff from entering drains, sewers or waterways. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Combustible liquid. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Use water spray to cool unopened containers. Move undamaged containers from immediate hazard area if it can be done safely. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. On burning: release of carbon monoxide - carbon dioxide. unburned hydrocarbons. Formaldehyde.

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothes. Avoid breathing dust, fume, mist, spray, vapors. Stop leak if safe to do so. Avoid contact with skin, eyes and clothing. Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Wear proper protective equipment. Keep upwind of the spilled material and isolate exposure. Do NOT touch spilled material. Cleanup personnel must be trained in the safe handling of this product. If possible ventilate area by means of non-sparking, grounded ventilation system. Spills may be absorbed on non-reactive absorbents such as vermiculite. Place cells into individual plastic bags and then place into appropriate containers and close tightly for disposal. Ensure that cleanup procedures do not expose spilled material to any moisture. Immediately transport closed containers outside. Contain large spillage with sand or earth. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Gather the product and place it in a spare container that has been suitably labelled. Store away from other materials. Consult the appropriate authorities about waste disposal. Eliminate all sources of ignition, avoid sparks, flames and do not smoke in risk area. Thoroughly wash the area with water after a spill or leak clean-up. Ensure all local, state, national and international regulations are observed.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, sparks, open flames, hot surfaces. - No smoking. Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Avoid contact with skin, eyes and clothing. Avoid breathing dust, fume, mist, spray, vapors. Work in a well-ventilated area. Use only outdoors or in a well-ventilated area. Provide good ventilation in process area to prevent formation of vapor. Before entering storage tanks and commencing any operation in a confined area check the atmosphere for oxygen content and flammability. . Keep away from clothing as well as other incompatible materials. No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use personal protective equipment as required.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practices. Discard contaminated leather articles. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : A washing facility for eye and skin cleaning purposes should be present. Ensure adequate ventilation. Use explosion-proof electrical, ventilating, lighting, and equipment. Proper grounding procedures to avoid static electricity should be followed. Ground container and receiving equipment. Comply with applicable regulations.

Storage conditions : Protect containers against physical damage. Keep only in the original container in a cool, well ventilated place. Store away from direct sunlight or other heat sources. Keep container tightly closed. Keep locked up and out of reach of children.

Incompatible materials : Strong acids, bases. Oxidizing agents.

Heat and ignition sources : Store away from direct sunlight or other heat sources.

7.3. Specific end use(s)

No additional information available

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl alcohol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

Phenol (108-95-2)		
USA ACGIH	ACGIH TWA (ppm)	5 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	19 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	5 ppm

Cresol, all isomers (1319-77-3)		
USA ACGIH	ACGIH TWA (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	22 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	5 ppm

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm

Ethylene glycol (107-21-1)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³

8.2. Exposure controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate ventilation. Monitoring the effectiveness of engineering control is recommended.
Personal protective equipment	: Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.
Hand protection	: Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Contact lenses should not be worn. Chemical goggles and face shields are required to prevent potential eye contact, irritation or injury.
Skin and body protection	: Long sleeved protective clothing. Overall. Rubber apron, boots, safety foot-wear.
Respiratory protection	: In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor respirator.
Environmental exposure controls	: Avoid discharge to the environment.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Very light pink
Odor	: Phenolic alcohol odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: > 1
Melting point	: No data available

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Freezing point	: No data available
Boiling point	: 65.55 °C (150 °F)
Flash point	: 38.33 °C (101 °F) (TCC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.965 Specific Gravity
Solubility	: Water: completely soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 25%
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. Unstable on exposure to heat. Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Oxidizing agents. Strong acids. strong bases.

10.6. Hazardous decomposition products

Thermal decomposition generates : Corrosive vapors. May release flammable gases. Fume. Carbon monoxide. Carbon dioxide. Formaldehyde.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Toxic if swallowed. Harmful in contact with skin. Harmful if inhaled.

Crisine-Ultra	
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	1100.00000000 mg/kg bodyweight
ATE US (dust,mist)	1.50000000 mg/l/4h
Methyl alcohol (67-56-1)	
LC50 inhalation rat (mg/l)	130.7 mg/l/4h (lit. ECHA)
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	300.00000000 mg/kg bodyweight
ATE US (vapors)	3.00000000 mg/l/4h
Phenol (108-95-2)	
LD50 dermal rabbit	630 mg/kg
ATE US (oral)	100.00000000 mg/kg bodyweight
ATE US (dermal)	630.00000000 mg/kg bodyweight

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Phenol (108-95-2)	
ATE US (gases)	700.00000000 ppmv/4h
ATE US (vapors)	3.00000000 mg/l/4h
ATE US (dust,mist)	0.50000000 mg/l/4h

Cresol, all isomers (1319-77-3)	
LD50 oral rat	1454 mg/kg
LD50 dermal rat	245 mg/kg
LD50 dermal rabbit	2000 mg/kg
ATE US (oral)	1454.00000000 mg/kg bodyweight
ATE US (dermal)	245.00000000 mg/kg bodyweight

Isopropyl alcohol (67-63-0)	
LD50 oral rat	4396 mg/kg
LD50 dermal rabbit	12800 mg/kg
LC50 inhalation rat (ppm)	16000 ppm (Exposure time: 8 h)
ATE US (oral)	4396.00000000 mg/kg bodyweight
ATE US (dermal)	12800.00000000 mg/kg bodyweight

Methyl salicylate (119-36-8)	
LD50 oral rat	887 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE US (oral)	887.00000000 mg/kg bodyweight

Ethylene glycol (107-21-1)	
LD50 oral rat	4000 mg/kg
ATE US (oral)	500.00000000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Suspected of causing genetic defects.
Carcinogenicity : Not classified

Phenol (108-95-2)	
IARC group	3 - Not classifiable

Cresol, all isomers (1319-77-3)	
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Isopropyl alcohol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Causes damage to organs (optic nerve, central nervous system).

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful in contact with skin. Harmful if inhaled. Toxic if swallowed.

Symptoms/injuries after inhalation : Harmful if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. Excessive concentrations may cause nervous system depression, headache, and weakness leading to unconsciousness. Causes damage to liver through prolonged or repeated exposure if inhaled. Difficulty in breathing. Product contains phenol. Inhalation of phenol vapors can lead to damage of the bronchial system and pulmonal oedema. Systemic damage to kidneys, liver and heart as well as neuropsychiatric disturbances are produced.

Symptoms/injuries after skin contact : Harmful in contact with skin. Absorbed through the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Contains phenol. Strong skin absorption as main danger of phenol poisoning at the workplace with paralysis of the central nervous system (with lethal consequences in severe cases) as well as liver and kidney damage. Phenol destroys the nerve endings in the skin. Therefore absence of pain does not necessarily mean the skin has been properly decontaminated.

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Symptoms/injuries after eye contact	: Redness and pain. Impaired vision, watering of eyes, defects in the cornea. Burning sensation. Inflammation. Can cause blindness. Causes serious eye damage.
Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Ingestion may cause nausea, vomiting and diarrhea. Swallowing can cause severe injury leading to death. Contains: Phenol and methanol. The swallowing of even a small amount of methanol can cause blindness or lead to death. The following may result in the case of a low dosage: nausea, headache, stomach-ache, vomiting and impaired vision (blurred vision, photophobia). There is furthermore risk of damage to liver, kidneys and heart. Effects may be delayed and manifest within 18 to 48 hours. Stinging sensation. Headache. Disorientation. Dizziness. Unconsciousness. Contains ethanol; constant ingestion of ethanol can lead to cirrhosis of the liver.

SECTION 12: Ecological information

12.1. Toxicity

Methyl alcohol (67-56-1)	
LC50 fishes 1	> 12700 mg/l 96 hours
EC50 Daphnia 1	> 10000 mg/l

Phenol (108-95-2)	
LC50 fishes 1	11.9 - 50.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	4.24 - 10.7 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	20.5 - 25.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	10.2 - 15.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Cresol, all isomers (1319-77-3)	
LC50 fishes 1	12.8 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Isopropyl alcohol (67-63-0)	
LC50 fishes 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Ethylene glycol (107-21-1)	
LC50 fishes 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

12.2. Persistence and degradability

Crisine-Ultra	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Crisine-Ultra	
Bioaccumulative potential	Not established.

Phenol (108-95-2)	
BCF fish 1	(no significant bioaccumulation)
Log Pow	1.47

Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)

Methyl salicylate (119-36-8)	
Log Pow	2.55

Ethylene glycol (107-21-1)	
Log Pow	-1.93

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	: No additional information available
-----------------------	---------------------------------------

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Consult the appropriate authorities about waste disposal. It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Ensure all local, state, national and international regulations are observed. Do not pressurize, cut, weld, braze solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Do not re-use empty containers. Dispose of contents and container to comply with applicable local, state, national and international regulation.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN2924, Flammable liquids, corrosive, n.o.s. (Isopropanol, Methanol, Phenol), 3, PGIII, ltd. qty.

Hazard labels (DOT) : 3 - Flammable liquid
8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Crisine-Ultra	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5055 lb
Methyl alcohol (67-56-1)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1.0 %
Phenol (108-95-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Phenol (108-95-2)	
SARA Section 302 Threshold Planning Quantity (TPQ)	500 - 10000
SARA Section 313 - Emission Reporting	1.0 %

Cresol, all isomers (1319-77-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 313 - Emission Reporting	1.0 %

Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 % (only if manufactured by the strong acid process, no supplier notification)

Ethylene glycol (107-21-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1.0 %

15.2. International regulations

CANADA

Phenol (108-95-2)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material

Cresol, all isomers (1319-77-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material

Isopropyl alcohol (67-63-0)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Methyl salicylate (119-36-8)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Ethylene glycol (107-21-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

NEW ZEALAND

HSNO Approval Number	HSR 002564
ERMA Group Standard	Embalming Products (Flammable, Toxic [6.1], Corrosive) Group Standard 2006

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

HSNO controls: Trigger quantities beyond which site and storage conditions apply:	
Location and transit depot test certification:	500 L (closed containers greater than 5 L) 1,500 L (closed containers up to and including 5 L) 250 L (open containers)
Hazardous atmosphere zone:	100 L (closed containers) 25 L (decanting) 5 L (open occasionally) 1 L (open container in continuous use)
Fire extinguishers:	500 L
Response plans and secondary containment:	100 L
Signage:	1,000 L
Approved handler test certificate:	Required for HSNO Class 6 substance
Tracking requirements:	6.1B substances must comply with the Hazardous Substances (Tracking) Regulations 2001.
This information is subject to the conditions and exceptions detailed in the relevant Group Standard available from http://ermanz.govt.nz/hs/groupstandards/index.html .	

EU-Regulations

Phenol (108-95-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Cresol, all isomers (1319-77-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isopropyl alcohol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Ethylene glycol (107-21-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

15.2.2. National regulations

Phenol (108-95-2)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)

Cresol, all isomers (1319-77-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Isopropyl alcohol (67-63-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

Ethylene glycol (107-21-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

No additional information available

Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 2	Flammable liquids Category 1 flammable liquids Category 4
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled

Crisine-Ultra

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 2 Moderate Hazard
Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.