

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012) Date of issue: February 2023 Version: 3.0

.1. Product identifier Trade name	: HPX			
	e substance or mixture and uses	•		
Use of the substance/mixture	: Arterial Embalming Flu			
Use of the substance/mixture	: For professional use o	nly		
.3. Details of the supplier of the s	afety data sheet			
THE CHAMPION COMPANY		Lucentt Limited		
100 Harrison Street Springfield, Ohio 45505		40 Ben Lomond Cres Auckland, New Zeala		
springheid, Onio 43303				
Felephone No. (937) 324-5681		Phone: 09 273 8114		
.4. Emergency telephone numbe				
NFOTRAC: 1-800-535-5053 DOMESTIC	or 352-323-3500 INTERNATIONA	L		
lational Poisons Centre 0800 764 766				
lazardous Substance Emergency 080	OCHEMCALL (0800 243 622)			
SECTION 2: Hazards identificat	on			
2.1. Classification of the substand				
GHS-US classification				
Flam. Liq. 4 H22	,			
Acute Tox. 3 (Oral) H30				
Acute Tox. 3 (Dermal) H31				
Acute Tox. 4 (Inhalation:dust,mist) H33				
Skin Irrit. 2H31Eye Dam. 1H31				
Resp. Sens. 1 H33				
Skin Sens. 1 H31				
Carc. 1A H35				
STOT SE 3 H33 STOT SE 1 H37				
	,			
2.2. Label elements				
GHS-US labelling				
Hazard pictograms (GHS-US)		\wedge		
		~~v i		
		\checkmark		
	_	GHS06 GHS07	GHS08	
Signal word (GHS-US)	: Danger			
Hazard statements (GHS-US)	: H227 - Combustible lid		ith allia	
	H301+H311 - Toxic ir H315 - Causes skin irr	swallowed or in contact w	ith skin	
	H317 - May cause an			
	H318 - Causes serious			
	H332 - Harmful if inha	led		
			or breathing difficulties if inhaled	
	H335 - May cause res			
	H350 - May cause car H370 - Causes damag			
Propositionary statements (CHS LIS)	: P201 - Obtain special	-		
Flecaulionally statements (Gho-tro)			have been read and understood	
Precautionary statements (GHS-US)				
Frecautionary statements (GHS-OS)	P210 - Keep away fror			
Frecaulionary statements (GFIS-03)	P210 - Keep away fror P260 - Do not breathe	dust, fume, mist, spray, v	apors	
Frecaulionary statements (GFIS-03)	P210 - Keep away fror P260 - Do not breathe P261 - Avoid breathing		apors	

P271 - Use only in a well-ventilated area P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective clothing, protective gloves, eye protection, face protection P285 - In case of inadequate ventilation wear respiratory protection P301+P310 - If swallowed: Immediately call a POISON CENTER P302+P352 - If on skin: Wash with plenty of water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P307+P311 - If exposed: Call a doctor P308+P313 - If exposed or concerned: Get medical attention P310 - Immediately call a doctor, a POISON CENTER P312 - Call a doctor if you feel unwell P330 - Rinse mouth P332+P313 - If skin irritation occurs: Get medical attention P333+P313 - If skin irritation or rash occurs: Get medical attention P342+P311 - If experiencing respiratory symptoms: Call a doctor P361 - Take off immediately all contaminated clothing P362 - Take off contaminated clothing and wash before reuse P363 - Wash contaminated clothing before reuse P370+P378 - In case of fire: Use alcohol resistant foam, dry powder, carbon dioxide (CO2) to extinguish P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents and container to comply with applicable local, state, national and international regulation.

2.3. **Other hazards**

	hazards which do not result in ification
24	Unknown acute toxicity ((

: Spills of this product present a serious slipping hazard.

e toxicity (GHS-US) Unknown

No data available

SECTION 3: Composition/information on ingredients

Substance 3.1.

Not applicable

3.2. **Mixture**

Name	Product identifier	%	GHS-US classification
Formaldehyde	(CAS No) 50-00-0	25	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335
Methyl alcohol	(CAS No) 67-56-1	10 - 22	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapor), H331 STOT SE 1, H370
Glutaraldehyde	(CAS No) 111-30-8	<3.5	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335
Boric acid, disodium salt, pentahydrate	(CAS No) 12179-04-3	<2.5	Repr. 1B, H360
Ethyl formate	(CAS No) 109-94-4	< 0.25	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 STOT SE 3, H335
Oils, cedarwood, Texan	(CAS No) 68990-83-0	< 0.25	Asp. Tox. 1, H304

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).	
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Give artificial respiration if necessary. Immediately get medical attention.	
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical attention.	
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.	
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Call a POISON CENTER. Obtain emergency medical attention. Give water or milk if the person is fully conscious. Never give anything by mouth to a person who is not fully conscious. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.	
4.2. Most important symptoms and ef	fects, both acute and delayed	
Symptoms/injuries	: Causes damage to organs.	
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes damage to liver through prolonged or repeated exposure if inhaled.	
Symptoms/injuries after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. Causes skin irritation. Redness. Dermatitis. Contains formaldehyde which can combine with epidermal protein to produce a hapten-protein couple capable of sensitising T-lymphocytes. Subsequent exposures cause a type IV hypersensitivity reaction.	
Symptoms/injuries after eye contact	: Causes serious eye damage. Can cause blindness.	
Symptoms/injuries after ingestion	: Toxic if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea and vomiting. Can cause blindness. Death in extreme cases. This material contains methanol, which, when ingested, has cards acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.	

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.
5.2. Special hazards arising from the subs	stance or mixture
Fire hazard	: Combustible liquid.
Explosion hazard	May form flammable/explosive vapor-air mixture. Heating will cause pressure rise with risk of bursting and subsequent explosion. Vapors can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.
5.3. Advice for firefighters	
Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus.
Other information	: Special danger of slipping by leaking and spilling product. Thermal combustion may release carbon monoxide and dioxide. unburned hydrocarbons. Toxic gases and fumes may be released in a fire. On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray. Combustible liquid. Explosive dust-air mixtures may form. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECT	ION 6: Accidental release meas	sure	es
6.1.	Personal precautions, protective equipment and emergency procedures		
Gener	al measures	:	Avoid breathing dust, fume, mist, spray, vapors. Stop leak if safe to do so. Surface will become slippery when wet or damp. No open flames. No smoking. Take precautionary measures against static discharge. Eliminate all ignition sources if safe to do so.
6.1.1.	For non-emergency personnel		
Emerç	gency procedures	:	Evacuate unnecessary personnel.
6.1.2.	For emergency responders		
Protec	ctive equipment	:	Equip cleanup crew with proper protection.
Emerç	gency procedures	:	Ventilate area.
6.2.	Environmental precautions		
Prevent	entry to sewers and public waters. Notify	aut	horities if liquid enters sewers or public waters.
6.3	Methods and material for containment and cleaning up		nd cleaning up

Methods for cleaning up :	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Collect all waste in suitable and labelled containers and dispose according to local legislation. Ensure all national and local regulations are observed. Thoroughly wash the area with water after a spill or leak clean-up. Dispose of waste according to applicable legislation. Incinerate, dispose in sanitary landfill - if permitted. Consult the appropriate authorities about waste disposal.
---------------------------	---

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Obtain special instructions before use. Avoid contact with skin and eyes. Work in a well-ventilated area. When not in use, keep containers tightly closed. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures	: Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practices.
7.2. Conditions for safe storage, including	g any incompatibilities
Technical measures	: Provide local exhaust or general room ventilation. A washing facility for eye and skin cleaning purposes should be present.
Storage conditions	: Keep out of reach of children. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Keep container tightly closed and dry. Store away from direct sunlight or other heat sources.
Incompatible materials	: Strong acids, bases. Oxidizing agents.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Boric acid, disodium salt, pentahydrate (12179-04-3)				
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (inhalable fraction)		
USA ACGIH	ACGIH STEL (mg/m³)	6 mg/m ³ (inhalable fraction)		
Glutaraldehyde (111-3	0-8)			
USA ACGIH	ACGIH Ceiling (ppm)	0.05 ppm (activated and inactivated)		
Formaldehyde (50-00-0	0)			
USA ACGIH	ACGIH Ceiling (ppm)	0.3 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	0.75 ppm		
USA OSHA	OSHA PEL (STEL) (ppm)	2 ppm (see 29 CFR 1910.1048)		
Methyl alcohol (67-56-	1)			
USA ACGIH	ACGIH TWA (ppm)	200 ppm		

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Methyl alcohol (67-56-1)		
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
Ethyl formate (109-94-	4)	
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	300 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. **Exposure controls**

Appropriate engineering controls	: Provide local exhaust or general room ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Personal protective equipment	 Avoid all unnecessary exposure. Wear protective clothing, protective gloves, eye protection/goggles, face protection. For certain operations, additional Personal Protection Equipment (PPE) may be required.
Hand protection	: Wear impermeable protective nitrile gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Contact lenses should not be worn. Chemical goggles and face shields are required to prevent potential eye contact, irritation or injury.
Skin and body protection	: Long sleeved protective clothing. Overall. Rubber apron, boots. safety foot-wear.
Respiratory protection	: In case of insufficient ventilation. Wear suitable respiratory equipment. Approved organic vapor respirator.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Color	: Pink	
Odor	: Pungent odor	
Odor threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butyl acetate=1)	: 1	
Melting point	: No data available	
Freezing point	: No data available	
Boiling point	: 93.33 °C (200 °F)	
Flash point	: 82.77 °C (181 °F COC)	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapor pressure	: No data available	
Relative vapor density at 20 °C	: ≈1	
Relative density	: No data available	
Density	: 1.06 Specific Gravity	
Solubility	: Water: completely soluble	
Log Pow	: No data available	
Log Kow	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: No data available	
Oxidising properties	: No data available	
Explosive limits	: 6.7 - 72 vol %	

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

9.2.	Other information		
VOC o	content	: 20 %	(Percent Volatiles)
SECT	ION 10: Stability and reactivity		
10.1.	Reactivity		
No addi	tional information available		
10.2.	Chemical stability		
Stable a	at normal conditions.		
10.3.	Possibility of hazardous reactions		
Hazard	ous polymerization will not occur.		
10.4.	Conditions to avoid		
Direct s	unlight. Extremely high or low temperature	es.	
10.5.	Incompatible materials		
Strong a	acids. Strong bases. Oxidizing agents.		

10.6. Hazardous decomposition products

On thermal combustion form: Fume. Carbon monoxide. Carbon dioxide. unburned hydrocarbons. Toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Toxic if swallowed. Toxic in contact with skin. Harmful if inhaled.

Boric acid, disodium salt, pentahydrate (12179-04-3)		
LD50 oral rat	2403 mg/kg	
ATE US (oral)	2403.0000000 mg/kg bodyweight	
Glutaraldehyde (111-30-8)		
LD50 oral rat	252 mg/kg	
LD50 dermal rabbit	560 μl/kg	
LC50 inhalation rat (mg/l)	0.1 mg/l/4h	
ATE US (oral)	252.0000000 mg/kg bodyweight	
ATE US (vapors)	0.1000000 mg/l/4h	
ATE US (dust,mist)	0.1000000 mg/l/4h	
Formaldehyde (50-00-0)		
LD50 oral rat	600 mg/kg	
LD50 dermal rabbit	270 mg/kg	
LC50 inhalation rat (mg/l)	0.578 mg/l/4h	
ATE US (oral)	100.0000000 mg/kg bodyweight	
ATE US (dermal)	270.0000000 mg/kg bodyweight	
ATE US (gases)	700.0000000 ppmv/4h	
ATE US (vapors)	0.57800000 mg/l/4h	
ATE US (dust,mist)	0.57800000 mg/l/4h	
Methyl alcohol (67-56-1)		
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)	
ATE US (oral)	100.0000000 mg/kg bodyweight	
ATE US (dermal)	300.0000000 mg/kg bodyweight	
ATE US (vapors)	3.0000000 mg/l/4h	
Ethyl formate (109-94-4)		
LD50 oral rat	1850 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	
ATE US (oral)	1850.0000000 mg/kg bodyweight	
ATE US (gases)	4500.0000000 ppmv/4h	
ATE US (vapors)	11.0000000 mg/l/4h	
ATE US (dust,mist)	1.5000000 mg/l/4h	

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Carcinogenicity	: May cause cancer.
Formaldehyde (50-00-0)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	2 - Known Human Carcinogens
Reproductive toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. Causes damage to organs.
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Assistion borord	: Not classified
Aspiration hazard	(Based on available data, the classification criteria are not met)
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Inhalation of concentrated vapors may cause serious damage to the lining of the nose, throat, and lungs. Depression of the central nervous system, headaches dizziness, drowsiness, loss of coordination. Difficulty in breathing. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation. Causes damage to liver through prolonged or repeated exposure if inhaled.
Symptoms/injuries after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skir causing significant health hazard. May cause an allergic skin reaction. Causes skin irritation Redness. Dermatitis. Contains formaldehyde which can combine with epidermal protein to produce a hapten-protein couple capable of sensitising T-lymphocytes. Subsequent exposures cause a type IV hypersensitivity reaction.
Symptoms/injuries after eye contact	: Causes serious eye damage. Can cause blindness.
Symptoms/injuries after ingestion	: Toxic if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea and vomiting. Can cause blindness. Death ir extreme cases. This material contains methanol, which, when ingested, has cards acidosis, ocula toxicity ranging from diminished visual capacity to complete blindness, and death.

utaraldehyde (111-30-8)	
C50 fishes 1	7.8 - 22 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.6 - 4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	0.56 - 1.0 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Formaldehyde (50-00-0)	
LC50 fishes 1	22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1510 µg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
.2. Persistence and degradability	
НРХ	
Persistence and degradability	Not established.
.3. Bioaccumulative potential	
НРХ	
Bioaccumulative potential	Not established.

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

ccording to the federal final rule of hazard communication revised on 2012 (HazCom 2012)			
Glutaraldehyde (111-30-8)			
Log Pow 0.22 (at 25 °C)			
Formaldehyde (50-00-0)			
Log Pow	0.35 (at 25 °C)		
Ethyl formate (109-94-4)			
BCF fish 1	(will not bioconcentrate)		
12.4. Mobility in soil			
No additional information available			
12.5. Other adverse effects			
Effect on ozone layer	: No additional information available		
·	: No additional information available		
Effect on the global warming			
Other information	: Avoid release to the environment.		
SECTION 13: Disposal considerations	s		
13.1. Waste treatment methods			
Waste disposal recommendations	: Dispose in a safe manner in accordance with local and national regulations. Incinerate, dispose in sanitary landfill - if permitted. Ensure all national and local regulations are observed.		
Additional information	: Do not re-use empty containers. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources.		
Ecology - waste materials	: Avoid release to the environment.		
SECTION 14: Transport information			
In accordance with DOT			
Transport document description	: UN2209, Formaldehyde, solutions, 8, PGIII, Itd.qty.		
Hazard labels (DOT)	: 8 - Corrosive		
	8		
Packing group (DOT)	: 11		
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154		
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203		
DOT Packaging Bulk (49 CFR 173.xxx)	: 241		
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	. 3L		
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L		
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.		
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"		
Additional information			
Other information	: No supplementary information available.		
Transport by sea No additional information available			
Air transport			
No additional information available			

Safety Data Sheet according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 15: Regulatory information		
5.1. US Federal regulations		
НРХ		
RQ (Reportable quantity, section 304 of EPA's L	ist of Lists)	431 lb
Formaldehyde (50-00-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on United States SARA Section 313		
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	500	
SARA Section 313 - Emission Reporting	0.1 %	
Methyl alcohol (67-56-1)		
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb	
SARA Section 313 - Emission Reporting	1.0 %	

15.2. International regulations CANADA

Glutaraldehyde (111-30-8)		
Listed on the Canadian DSL (Domes	tic Sustances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material	
Formaldehyde (50-00-0)		
Listed on the Canadian DSL (Domes	tic Sustances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Ethyl formate (109-94-4)		
Listed on the Canadian DSL (Domestic Sustances List)		

	Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification Class B Division 2 - Flammable Liquid			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects		

NEW ZEALAND

HSNO Approval Number	HSR 002567	
ERMA Group Standard	Embalming Products (Flammable, Toxic [6.1], Corrosive) Group Standard 2006	
HSNO controls: Trigger qua	antities beyond which site and storage conditions apply:	
Fire extinguishers:	500 L	
Response plans and secor	ndary containment: 100 L	
Signage:	250 L	
Approved handler test certi	ificate: Required for HSNO Class 6 substance	
Tracking requirements:	6.1B substances must comply with the Hazardous Substances (Tracking) Regulations 2001.	
This information is subject to the conditions and exceptions detailed in the relevant Group Standard available from http://ermanz.govt.nz/hs/groupstandards/index.html.		

EU-Regulations

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Formaldehyde (50-00-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP] No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

15.2.2. National regulations

Formaldehyde (50-00-0)

Listed on IARC (International Agency for Research on Cancer)

Listed on the AICS (Australian Inventory of Chemical Substances)

- Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
- Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
- Listed on the Japanese ISHL (Industrial Safety and Health Law)
- Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed as carcinogen on NTP (National Toxicology Program)

Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Formaldehyde (50-00-0)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
Methyl alcohol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

SECTION 16: Other information

Other information

: None.

Full text of H-phrases: see section 16:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Resp. Sens. 1	Sensitisation — Respiratory, category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Sensitisation — Skin, category 1

HPX Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H360	May damage fertility or the unborn child
H370	Causes damage to organs

HMIS III Rating

Health Flammability

: 2 Moderate Hazard

Physical

: 0 Minimal Hazard

SDS US (GHS HazCom 2012)

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

: 2 Moderate Hazard - Temporary or minor injury may occur